

RM4000-2

RAINS TO MAINS SYSTEM - FLOATLESS

The RainPro® RM4000-2 system is designed for speed of installation - no cables, no float, no solenoid, no electronic controls. The simplicity of this system has the added benefit of making it very affordable. The RM4000-2 restricts flow of mains supply while rain water is in the tank to help conserve our precious resource. This system is suited for applications supplying laundry and toilets only. For whole house supply use the RM2500-2. This system is not suitable for suction lift, use the RM5000-2 submersible version for underground tanks.

CODE	MODEL	RATED		MAXIMUM	
		FLOW (L/min)	HEAD (m)	FLOW (L/min)	HEAD (m)
5699	RM4000-2 Rains to Main Controller with PRJ062 Pressure Pump	25	20	62	35
5934	RM4000-2 Rains to Main Controller with PRJ075 Pressure Pump	40	27	76	42

Applications

- Domestic toilet and/or laundry supply
- Small house/cabin supply (1 bathroom)
- Garden irrigation

Benefits

- Rains to Mains switch over system allows mains water to flow if tank water is unavailable, and restricts mains flow if tank water is sufficient.
- Watermark certified
- Reliable, efficient power-saving performance
- Automatic Pressure Controller giving consistent pressure supply, and automatically checks for water every 24 hours after a run dry event
- Run-dry protection and thermal overload protection to protect the Pump

Construction

- Stainless-steel Casing and Shaft
- Carbon/Ceramic Mechanical Seal for reliability
- IP44 Motor with B-class Insulation
- Quick plug Pressure Controller connection
- Stainless Steel Housing
- Noryl Jet and Venturi, Diffuser and Impeller

